

MBS REALbasic DotMacKit Plugin Documentation

Christian Schmitz

January 17, 2011

0.1 Introduction

This is the PDF version of the documentation for the REALbasic Plug-in from Monkeybread Software Germany. Plugin part: MBS REALbasic DotMacKit Plugin

0.2 Content

- 1 List of all topics 3
- 2 All items in this plugin 11
- 3 List of all classes 95
- 4 List of all global methods 97

Chapter 1

List of Topics

• 2 DotMacSDK	11
– 2.3 class DMMessagePublisherMBS	20
* 2.3.1 Constructor(credentials as DMMemberAccountMBS)	20
* 2.3.1 createTopicNamed(topicName as string) as DMTransactionMBS	20
* 2.3.1 credentials as DMMemberAccountMBS	21
* 2.3.1 defaultTimeToLive as double	21
* 2.3.1 isSynchronous as boolean	21
* 2.3.1 kDMModify as string	22
* 2.3.1 kDMRead as string	22
* 2.3.1 kDMReadChildren as string	22
* 2.3.1 kDMWrite as string	23
* 2.3.1 messagePublisherWithCredentials(credentials as DMMemberAccountMBS) as DMMessagePublisherMBS	23
* 2.3.1 publishMessage(message as DMMessageMBS, topic as DMTopicMBS) as DMTransactionMBS	23
* 2.3.1 removeTopicNamed(topicName as string) as DMTransactionMBS	24
* 2.3.1 topicNamed(name as string) as DMTopicMBS	24
* 2.3.1 topicNamed(name as string, memberName as string) as DMTopicMBS	24
* 2.3.1 topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS	25
* 2.3.1 topics as DMTransactionMBS	25
* 2.3.1 transactionDelegate as DMTransactionDelegateMBS	26
* 2.3.2 Handle as Integer	26
* 2.3.3 kDMInsufficientStorage=102	27
* 2.3.3 kDMInvalidCredentials=101	27
* 2.3.3 kDMNetworkError=103	27

* 2.3.3 kDMResourceExists=105	27
* 2.3.3 kDMResourceNotFound=104	28
* 2.3.3 kDMServiceBusy=106	28
* 2.3.3 kDMSuccess=1	28
– 2.1 class DMMessageSubscriberMBS	11
* 2.1.1 Constructor(credentials as DMMemberAccountMBS)	11
* 2.1.1 credentials as DMMemberAccountMBS	12
* 2.1.1 messagePublisherWithCredentials(credentials as DMMemberAccountMBS) as DMMessageSubscriberMBS	12
* 2.1.1 subscribeToTopic(topic as DMTopicMBS) as DMTransactionMBS	12
* 2.1.1 topicNamed(name as string) as DMTopicMBS	13
* 2.1.1 topicNamed(name as string, memberName as string) as DMTopicMBS	13
* 2.1.1 topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS	14
* 2.1.1 unsubscribeFromTopic(topic as DMTopicMBS) as DMTransactionMBS	14
* 2.1.2 Handle as Integer	14
* 2.1.3 kDMLaunchAlways = 1	15
* 2.1.3 kDMLaunchDefault = 0	15
* 2.1.3 kDMLaunchInBackground = 2	15
– 2.2 class DMSecondaryUserMBS	16
* 2.2.1 Constructor(name as string, password as string, owner as string, applicationID as string)	16
* 2.2.1 isSynchronous as boolean	17
* 2.2.1 name as string	17
* 2.2.1 owner as string	17
* 2.2.1 password as string	18
* 2.2.1 principalID as string	18
* 2.2.1 principalIDWithName(name as string, memberName as string) as string	18
* 2.2.1 secondaryUserWithName(name as string, password as string, owner as string, applicationID as string) as DMSecondaryUserMBS	18
* 2.2.1 transactionDelegate as DMTransactionDelegateMBS	19
* 2.2.2 Handle as Integer	19
– 2.11 class DMMessageMBS	74
* 2.11.1 Constructor(messageString as string)	74
* 2.11.1 expirationDate as date	75
* 2.11.1 isPublished as boolean	75
* 2.11.1 isSynchronous as boolean	75
* 2.11.1 messageID as string	76
* 2.11.1 messageString as string	76
* 2.11.1 payload as DMTransactionMBS	76
* 2.11.1 payloadType as string	76

* 2.11.1 properties as dictionary	77
* 2.11.1 publicationDate as date	77
* 2.11.1 publisher as string	77
* 2.11.1 setMessageString(messageString as string) as integer	77
* 2.11.1 setProperties(dic as dictionary) as integer	78
* 2.11.1 setTimeToLive(timeToLive as double) as integer	78
* 2.11.1 timeToLive as double	78
* 2.11.1 topic as DMTopicMBS	79
* 2.11.1 transactionDelegate as DMTransactionDelegateMBS	79
* 2.11.2 Handle as Integer	79
* 2.11.3 kDMInsufficientStorage=102	80
* 2.11.3 kDMInvalidCredentials=101	80
* 2.11.3 kDMNetworkError=103	80
* 2.11.3 kDMResourceExists=105	80
* 2.11.3 kDMResourceNotFound=104	81
* 2.11.3 kDMServiceBusy=106	81
* 2.11.3 kDMSuccess=1	81
– 2.4 class DMTransactionMBS	28
* 2.4.1 abort	29
* 2.4.1 bytesTransferred as Int64	29
* 2.4.1 contentLength as Int64	29
* 2.4.1 DictionaryResult as dictionary	29
* 2.4.1 errorType as integer	30
* 2.4.1 httpStatusCode as integer	30
* 2.4.1 IsDictionaryResult as boolean	31
* 2.4.1 isFinished as boolean	31
* 2.4.1 IsNumberResult as boolean	31
* 2.4.1 IsStringArrayResult as boolean	31
* 2.4.1 IsStringResult as boolean	31
* 2.4.1 isSuccessful as boolean	32
* 2.4.1 NumberResult as double	32
* 2.4.1 Result as variant	32
* 2.4.1 StringArrayResult as string()	32
* 2.4.1 StringResult as string	33
* 2.4.1 transactionID as string	33
* 2.4.1 transactionState as integer	33
* 2.4.1 uri as string	34
* 2.4.2 context as variant	34
* 2.4.2 Handle as Integer	34
* 2.4.3 kDMTransactionAborted=4	35
* 2.4.3 kDMTransactionActive=2	35

* 2.4.3 kDMTransactionHadError=5	35
* 2.4.3 kDMTransactionNotStarted=1	35
* 2.4.3 kDMTransactionSuccessful=3	36
– 2.7 class DMTransactionDelegateMBS	42
* 2.7.1 Constructor	42
* 2.7.2 Handle as Integer	43
* 2.7.3 transactionAborted(Transaction as DMTransactionMBS)	43
* 2.7.3 transactionHadError(Transaction as DMTransactionMBS)	43
* 2.7.3 transactionSuccessful(Transaction as DMTransactionMBS)	44
– 2.5 Globals	36
* 2.5 LoadDotMacKitFrameworkMBS(path as folderitem) as boolean	36
– 2.6 class DMTopicMBS	36
* 2.6.1 applicationID as string	37
* 2.6.1 credentials as DMMemberAccountMBS	37
* 2.6.1 exists as DMTransactionMBS	37
* 2.6.1 isAutoArrivalEnabledForMessagePayloads as boolean	38
* 2.6.1 isSynchronous as boolean	38
* 2.6.1 messages as DMMessageMBS()	39
* 2.6.1 messageWithID(messageID as string) as DMMessageMBS	39
* 2.6.1 name as string	39
* 2.6.1 newestMessage as DMMessageMBS	40
* 2.6.1 newMessages as DMMessageMBS()	40
* 2.6.1 oldestMessage as DMMessageMBS	40
* 2.6.1 owner as string	40
* 2.6.1 removeMessages as DMTransactionMBS	41
* 2.6.1 removeMessageWithID(messageID as string) as DMTransactionMBS	41
* 2.6.1 resetTimeToLive(ttl as double, messageID as string) as DMTransactionMBS	41
* 2.6.1 transactionDelegate as DMTransactionDelegateMBS	41
* 2.6.2 Handle as Integer	42
– 2.9 class DMiDiskSessionMBS	47
* 2.9.1 account as DMAccountMBS	48
* 2.9.1 basicAttributesAtPath(path as string) as DMTransactionMBS	48
* 2.9.1 Constructor(c as DMAccountMBS) as DMiDiskSessionMBS	49
* 2.9.1 Constructor(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS	49
* 2.9.1 Constructor(c as DMSecondaryUserMBS) as DMiDiskSessionMBS	49
* 2.9.1 Constructor(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS	50
* 2.9.1 contentsAtPath(path as string) as string	50
* 2.9.1 copyPath(source as string, destination as string) as boolean	50
* 2.9.1 copyResourceAtPath(sourcePath as string, destinationPath as string) as DMTransactionMBS	51

* 2.9.1 createDirectoryAtPath(path as string) as boolean	51
* 2.9.1 createFileAtPath(path as string, content as string) as boolean	52
* 2.9.1 credentials as variant	52
* 2.9.1 defaultLockDuration as double	52
* 2.9.1 deleteResourceAtPath(path as string) as DMTransactionMBS	53
* 2.9.1 directoryContentsAtPath(Path as string) as string()	53
* 2.9.1 extendedAttributesAtPath(path as string) as DMTransactionMBS	53
* 2.9.1 fileExistsAtPath(path as string) as boolean	54
* 2.9.1 fileExistsAtPath(path as string, byref isDirectory as boolean) as boolean	54
* 2.9.1 getDataAtPath(path as string) as DMTransactionMBS	55
* 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date) as DMTransactionMBS	55
* 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date, ByteStart as double, ByteLength as double) as DMTransactionMBS	55
* 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS) as DMiDiskSessionMBS	56
* 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS	56
* 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS) as DMiDiskSessionMBS	57
* 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS	57
* 2.9.1 isSynchronous as boolean	58
* 2.9.1 kDMModify as string	58
* 2.9.1 kDMRead as string	58
* 2.9.1 kDMReadChildren as string	59
* 2.9.1 kDMWrite as string	59
* 2.9.1 listCollectionAtPath(path as string) as DMTransactionMBS	59
* 2.9.1 lockResourceAtPath(path as string) as DMTransactionMBS	59
* 2.9.1 lockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS	60
* 2.9.1 makeCollectionAtPath(path as string) as DMTransactionMBS	61
* 2.9.1 movePath(source as string, destination as string) as boolean	61
* 2.9.1 moveResourceAtPath(sourcePath as string, destinationPath as string) as DMTransactionMBS	61
* 2.9.1 owner as string	62
* 2.9.1 putData(data as string, destinationPath as string) as DMTransactionMBS	62
* 2.9.1 putData(data as string, destinationPath as string, ByteStart as double, ByteLength as double) as DMTransactionMBS	62
* 2.9.1 putLocalFileAtPath(localPath as string, destinationPath as string) as DMTransactionMBS	63
* 2.9.1 quotaAttributes as DMTransactionMBS	63
* 2.9.1 relockResourceAtPath(path as string) as DMTransactionMBS	64
* 2.9.1 relockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS	64
* 2.9.1 removeFileAtPath(path as string) as boolean	65

* 2.9.1 resourceExistsAtPath(path as string) as boolean	65
* 2.9.1 transactionDelegate as DMTransactionDelegateMBS	65
* 2.9.1 unlockResourceAtPath(path as string) as DMTransactionMBS	66
* 2.9.2 Handle as Integer	66
* 2.9.3 kDMContentLength = "DAV:getcontentlength"	66
* 2.9.3 kDMContentType = "DAV:getcontenttype"	67
* 2.9.3 kDMDateCreated = "DAV:creationdate"	67
* 2.9.3 kDMDebugLogging = "DMDebugLogging"	67
* 2.9.3 kDMDisplayName = "DAV:displayname"	67
* 2.9.3 kDMErrorLogging = "DMErrorLogging"	67
* 2.9.3 kDMGroup = "Group"	68
* 2.9.3 kDMiDiskQuotaInBytes = "DAV:quota"	68
* 2.9.3 kDMiDiskSpaceUsedInBytes = "DAV:quotaused"	68
* 2.9.3 kDMIsCollection = "IsCollection"	68
* 2.9.3 kDMIsLocked = "IsLocked"	69
* 2.9.3 kDMLastModified = "DAV:getlastmodified"	69
* 2.9.3 kDMLockOwner = "LockOwner"	69
* 2.9.3 kDMLockTimeout = "LockTimeout"	69
* 2.9.3 kDMLockToken = "LockToken"	70
* 2.9.3 kDMLoggingLevel = "com.apple.DotMacKit.LoggingLevel"	70
* 2.9.3 kDMMemberAccount = ".Mac Member"	70
* 2.9.3 kDMPrincipalName = "PrincipalName"	70
* 2.9.3 kDMPrincipalOwner = "PrincipalOwner"	71
* 2.9.3 kDMPrincipalType = "PrincipalType"	71
* 2.9.3 kDMSecondaryUser = "Secondary User"	71
* 2.9.3 kDMURI = "URI"	71
– 2.8 class DMGroupMBS	44
* 2.8.1 addMembers(members() as string) as DMTransactionMBS	44
* 2.8.1 isSynchronous as boolean	45
* 2.8.1 members as DMTransactionMBS	45
* 2.8.1 name as string	45
* 2.8.1 owner as string	46
* 2.8.1 principalID as string	46
* 2.8.1 principalIDWithName(name as string, memberName as string) as string	46
* 2.8.1 removeMembers(members() as string) as DMTransactionMBS	46
* 2.8.1 transactionDelegate as DMTransactionDelegateMBS	47
* 2.8.2 Handle as Integer	47
– 2.10 class DMAccountMBS	72
* 2.10.1 applicationID as string	72
* 2.10.1 applicationName as string	72
* 2.10.1 name as string	72

* 2.10.1 owner as string	73
* 2.10.1 password as string	73
* 2.10.1 principalID as string	73
* 2.10.1 principalIDWithName(name as string, memberName as string) as string	73
* 2.10.2 Handle as Integer	74
– 2.12 class DMMemberAccountMBS	81
* 2.12.1 accountFromPreferencesWithApplicationID(creatorCode as string) as DMMemberAccountMBS	82
* 2.12.1 accountUpgradeURL as string	82
* 2.12.1 accountWithName(name as string, password as string, creatorCode as string) as DMMemberAccountMBS	82
* 2.12.1 canUpgradeAccount as DMTransactionMBS	83
* 2.12.1 Constructor(creatorCode as string)	83
* 2.12.1 Constructor(name as string, password as string, creatorCode as string)	83
* 2.12.1 createGroupWithName(name as string, members() as string) as DMTransactionMBS	84
* 2.12.1 createSecondaryUserWithName(name as string, password as string) as DMTransactionMBS	84
* 2.12.1 daysLeftUntilExpiration as DMTransactionMBS	85
* 2.12.1 groupNamed(name as string) as DMGroupMBS	85
* 2.12.1 groupNames as DMTransactionMBS	85
* 2.12.1 isSynchronous as boolean	85
* 2.12.1 matchesSystemCredentials as boolean	86
* 2.12.1 removeGroupNamed(name as string) as DMTransactionMBS	86
* 2.12.1 removeSecondaryUserNamed(name as string) as DMTransactionMBS	86
* 2.12.1 resetPassword(password as string, SecondaryUserNamed as string) as DMTransactionMBS	87
* 2.12.1 secondaryUserNames as DMTransactionMBS	87
* 2.12.1 servicesAvailableForAccount as DMTransactionMBS	87
* 2.12.1 signUpNewMember	88
* 2.12.1 signUpNewMemberWithApplicationID(appID as string)	88
* 2.12.1 signUpURL as string	88
* 2.12.1 signUpURLWithApplicationID(appID as string) as string	89
* 2.12.1 transactionDelegate as DMTransactionDelegateMBS	89
* 2.12.1 upgradeAccount	89
* 2.12.1 validateCredentials as integer	90
* 2.12.2 kDMBackupService = "Backup"	90
* 2.12.2 kDMEmailService = "Email"	90
* 2.12.2 kDMiDiskService = "iDisk"	90
* 2.12.2 kDMInsufficientStorage=102	91
* 2.12.2 kDMInvalidCredentials=101	91
* 2.12.2 kDMInvalidParameter=107	91

* 2.12.2 kDMiSyncService = "iSync"	91
* 2.12.2 kDMNetworkError=103	92
* 2.12.2 kDMResourceExists=105	92
* 2.12.2 kDMResourceNotFound=104	92
* 2.12.2 kDMServiceBusy=106	92
* 2.12.2 kDMSuccess=1	93
* 2.12.2 kDMUndefined=-1	93
* 2.12.2 kDMUnknownError=100	93
* 2.12.2 kDMWebHostingService = "WebHosting"	93

Chapter 2

DotMacSDK

2.1 class DMMMessageSubscriberMBS

class DMMMessageSubscriberMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a message subscriber.

Notes: The thread-safe DMMMessageSubscriber session object is used to subscribe to specific topics and to access new messages in topics of interest. The .Mac credentials held by the DMMMessageSubscriber session represent the subscriber. The subscriber can subscribe to topics that it itself owns and to accessible topics owned by other .Mac members. [Note: Only .Mac members can publish or subscribe to messages. Currently, secondary users cannot.]

2.1.1 Methods

Constructor(credentials as DMMMemberAccountMBS)

method from class DMMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates an initialized DMMMessageSubscriber session that will use the provided objects creden-

tials when subscribing to DMTopics or accessing a DMTopics messages.

Notes: The provided .Mac member credentials can be used to subscribe to accessible topics owned by any .Mac member.

credentials as DMMemberAccountMBS

method from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the .Mac member object containing the credentials set for this DMMessagePublisher session.

Notes: These credentials are used to determine which topics can be subscribed to using this session.

messagePublisherWithCredentials(credentials as DMMemberAccountMBS) as DMMessageSubscriberMBS

shared method from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a new DMMessageSubscriber session that will use the provided objects credentials when subscribing to DMTopics or accessing a DMTopics messages.

Notes: The provided .Mac member credentials can be used to subscribe to accessible topics owned by any .Mac member.

subscribeToTopic(topic as DMTopicMBS) as DMTransactionMBS

method from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates a persistent subscription to the given topic.

Notes: This subscription is specific to this session's .Mac member credentials, the machine and local OS X user that the calling application is running under and the calling application itself. As an argument, this method takes a DMTopic to which this session's .Mac member credentials have access. Calling this method creates an entry for the given subscription in the local user preferences, which will cause the subscription to be reactivated every time the calling application runs and creates a DMMessageSubscriber object. Therefore,

subscribeToTopic only needs to be called once for a given topic by an application. Calling unsubscribeFromTopic removes the persistent subscription from the preferences. This method returns a DMTransaction object whose -isSuccessful method can be used to test for success.

topicNamed(name as string) as DMTopicMBS

method from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an autoreleased DMTopic instance with the provided name.

Notes: The returned topic's owner will be the .Mac member name specified by this DMMessageSubscribers credentials and the topics application ID will be set to the calling applications creator code. This method is used to obtain a DMTopic object that represents an existing topic on .Mac. The credentials set for this DMMessageSubscriber instance will be used to access the topic represented by the returned DMTopic object. To access messages in a topic, a DMTopic object is required. If you are trying to obtain a DMTopic object that represents a topic not owned by this DMMessageSubscriber's credentials, use the other topicNamed methods, as described below.

See also:

- 2.1.1 topicNamed(name as string, memberName as string) as DMTopicMBS 13
- 2.1.1 topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS 14

topicNamed(name as string, memberName as string) as DMTopicMBS

method from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an DMTopic instance with the provided name and owner, where the owner is the name of the .Mac member who hosts the given topic.

Notes: The returned topic's application ID will be set to the calling applications creator code. This method is used to obtain a DMTopic object that represents an existing topic on .Mac. The credentials set for this DMMessageSubscriber instance will be used to access the topic represented by the returned DMTopic object. To access messages in a topic, a DMTopic object is required. If you are trying to obtain a DMTopic object that represents a topic that was created by an application different from the calling application, use the topicNamed method, as described below.

See also:

- 2.1.1 topicNamed(name as string) as DMTopicMBS 13

- 2.1.1 `topicNamed(name as string, memberName as string, creatorCode as string)` as `DMTopicMBS` 14

topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS

method from class `DMMMessageSubscriberMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a `DMTopic` instance with the provided name, owner and application ID, where the owner is the name of the `.Mac` member who hosts the given topic and the application ID is the creator code of the application that originally created the given topic.

Notes: This method is used to obtain a `DMTopic` object that represents an existing topic on `.Mac`. The credentials set for this `DMMMessageSubscriber` instance will be used to access the topic represented by the returned `DMTopic` object. To access messages in a topic, a `DMTopic` object is required.

See also:

- 2.1.1 `topicNamed(name as string)` as `DMTopicMBS` 13
- 2.1.1 `topicNamed(name as string, memberName as string)` as `DMTopicMBS` 13

unsubscribeFromTopic(topic as DMTopicMBS) as DMTransactionMBS

method from class `DMMMessageSubscriberMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes an existing subscription to the given topic.

Notes: Removes a subscription specific to the `.Mac` member for this session, the machine and local OS X user that the calling application is running under and the calling application itself. Calling this method deletes the entry for the given subscription from the local user preferences. As an argument, this method takes a `DMTopic` object to which this session's `.Mac` member credentials have access. Returns a `DMTransaction` object whose `isSuccessful` method can be used to test for success.

2.1.2 Properties

Handle as Integer

property from class `DMMMessageSubscriberMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does

nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.1.3 Constants

kDMLaunchAlways = 1

const from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the auto-launch constants.

Notes:

Auto-launch constants are used for passing launch options to DMMessageSubscriber methods that schedule applications and tools to launch when a given topic changes (these launch options can be ord together as appropriate).

Always launch a new instance of application (applies to bundled apps only).

kDMLaunchDefault = 0

const from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the auto-launch constants.

Notes:

Auto-launch constants are used for passing launch options to DMMessageSubscriber methods that schedule applications and tools to launch when a given topic changes (these launch options can be ord together as appropriate).

Only one instance, launch in foreground.

kDMLaunchInBackground = 2

const from class DMMessageSubscriberMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the auto-launch constants.

Notes:

Auto-launch constants are used for passing launch options to `DMMessageSubscriber` methods that schedule applications and tools to launch when a given topic changes (these launch options can be ord together as appropriate).

Dont bring launched app to foreground (applies to bundled apps only).

2.2 class `DMSecondaryUserMBS`

class `DMSecondaryUserMBS`

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a secondary user.

2.2.1 Methods

Constructor(name as string, password as string, owner as string, applicationID as string)

method from class `DMSecondaryUserMBS`, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates a newly initialized `DMSecondaryUser` object keyed to a specific applications identification string.

Notes:

The secondary user is owned by the .Mac member with the given member name. Pass the unique 4-character application identifier obtained from

<http://developer.apple.com/datatype/creatorcode.html>

isSynchronous as boolean

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]
(Read and Write computed property)

name as string

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A username string is returned.

owner as string

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The name of the .Mac member who owns the credential is returned.

password as string

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A password string is returned.

principalID as string

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method is implemented by DMMemberAccount, DMSecondaryUser or DMGroup and returns the appropriate principal ID string.

principalIDWithName(name as string, memberName as string) as string

shared method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a principal ID string identifying the principal with the given name and owner (the owner is the name of the .Mac member that owns the given principal).

Notes: This class method is useful when the caller needs to obtain a principle ID representing a DMMemberAccount, DMSecondaryUser or DMGroup without creating an instance of one of those classes.

secondaryUserWithName(name as string, password as string, owner as string, applicationID as string) as DMSecondaryUserMBS

shared method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an autoreleased instance of DMSecondaryUser keyed to a specific applications identification string.

Notes:

The secondary user is owned by the .Mac member with the given member name. Pass the unique 4-character application identifier obtained from

<http://developer.apple.com/datatype/creatorcode.html>

transactionDelegate as DMTransactionDelegateMBS

method from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

2.2.2 Properties

Handle as Integer

property from class DMSecondaryUserMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.3 class DMMessagePublisherMBS

class DMMessagePublisherMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a message publisher.

Notes: The DMMessagePublisher session object is used to publish DMMessages to DMTopics and is thread-safe. The .Mac member credential held by the DMMessagePublisher session represents the member who will be publishing messages to topics. The publishing member can publish messages to topics that it itself owns or to topics owned by other .Mac members. The DMMessagePublisher session conforms to the DMSecurity protocol and DMTopics are considered securable entities that can be passed to DMSecurity methods for this session. [Note: Only .Mac members can publish or subscribe to messages. Currently, secondary users cannot.]

2.3.1 Methods

Constructor(credentials as DMMemberAccountMBS)

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates a newly initialized DMMessagePublisher session that will use the provided objects credentials when publishing DMMessages or otherwise accessing or modifying DMTopics.

Notes: The publishing member can publish messages to topics that it itself owns or to topics owned by other .Mac members.

createTopicNamed(topicName as string) as DMTransactionMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Adds a new, empty DMTopic to .Mac. The new topic will be owned by the .Mac member specified by this DMMessagePublishers credentials.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success.

credentials as DMMemberAccountMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the .Mac member object containing the credentials set for this DMMessagePublisher session.

Notes: These credentials are used to determine which topics can have messages published to them or be otherwise modified using this session.

defaultTimeToLive as double

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The default time-to-live that will be used by all DMMessages published by this session.

Notes:

The default time-to-live value is 7 days. Returns an NSTimeInterval (precision in seconds).

Sets the default time-to-live that will be used by all DMMessages published by this session. The default time-to-live value cannot exceed 30 days. Takes an NSTimeInterval (precision in seconds). If the provided ttl value not in the valid range, kDMInvalidParameter will be returned; otherwise, this method returns kDMSuccess.

(Read and Write computed property)

isSynchronous as boolean

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]

(Read and Write computed property)

kDMModify as string

shared method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes modify access to a given entity. Does not include create or delete access.

kDMRead as string

shared method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes read and list access to a given entity.

kDMReadChildren as string

shared method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes read and list access to children of a given entity only. Does not include read and list access

to the entity itself.

kDMWrite as string

shared method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes create, modify and delete access to a given entity.

messagePublisherWithCredentials(credentials as DMMemberAccountMBS) as DMMessagePublisherMBS

shared method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates a DMMessagePublisher session that will use the provided objects credentials when publishing DMMessages or otherwise accessing or modifying DMTopics.

Notes: The publishing member can publish messages to topics that it itself owns or to topics owned by other .Mac members.

publishMessage(message as DMMessageMBS, topic as DMTopicMBS) as DMTransactionMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Publishes a new DMMessage to a DMTopic that already exists on .Mac (an existing topic will have been previously created on .Mac by the topics owner using DMMessagePublishers createTopicNamed method).

Notes: The default timetolive for a newly published DMMessage is 7 days. This default can be overridden using the sessions setDefaultTimeToLive: method. Timetolive can also be set on a messageby message basis using DMMessages setTimeToLive: method. This method returns a DMTransaction object whose isSuccessfull method can be used to test for success. [Note: If .Mac is too busy to handle the message publication request, kDMServiceBusy will be returned by the transactions errorType method, and publication should be retried later. If the given DMMessage has already been published to .Mac, kDMResourceExists will be

returned by the transactions `errorType` method.]

removeTopicNamed(topicName as string) as DMTransactionMBS

method from class `DMMessagePublisherMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes the named `DMTopic` from `.Mac`, including all of the messages it contains.

Notes: A topic can be removed only by its owner, using the same application that originally created it. Therefore, the `.Mac` member name specified by this `DMMessagePublishers` credentials must be the owner of the topic and the calling application must be the same application used to originally create the topic. Returns a `DMTransaction` object whose `isSuccessful` method can be used to test for success.

topicNamed(name as string) as DMTopicMBS

method from class `DMMessagePublisherMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an autoreleased `DMTopic` instance with the provided name.

Notes: The returned topic's owner will be the `.Mac` member name specified by this `DMMessagePublishers` credentials and the topics application ID will be set to the calling applications creator code. This method is used to obtain a `DMTopic` object that represents an existing topic on `.Mac`. The credentials set for this `DMMessagePublisher` instance will be used to access or modify the topic represented by the returned `DMTopic` object. To publish messages to a topic or to list the messages in a topic, a `DMTopic` object is required. If you are trying to obtain a `DMTopic` object that represents a topic not owned by this `DMMessagePublisher`'s credentials.

See also:

- 2.3.1 `topicNamed(name as string, memberName as string) as DMTopicMBS` 24
- 2.3.1 `topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS` 25

topicNamed(name as string, memberName as string) as DMTopicMBS

method from class `DMMessagePublisherMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an autoreleased DMTopic instance with the provided name and owner, where the owner is the name of the .Mac member who hosts the given topic.

Notes: The returned topic's application ID will be set to the calling applications creator code. This method is used to obtain a DMTopic object that represents an existing topic on .Mac. The credentials set for this DMMessagePublisher instance will be used to access or modify the topic represented by the returned DMTopic object. To publish messages to a topic or to list the messages in a topic, a DMTopic object is required. If you are trying to obtain a DMTopic object that represents a topic that was created by an application different from the calling application, use the topicNamed method, as described below.

See also:

- 2.3.1 topicNamed(name as string) as DMTopicMBS 24
- 2.3.1 topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS 25

topicNamed(name as string, memberName as string, creatorCode as string) as DMTopicMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an autoreleased DMTopic instance with the provided name, owner and application ID, where the owner is the name of the .Mac member who hosts the given topic and the application ID is the creator code of the application that originally created the topic.

Notes: This method is used to obtain a DMTopic object that represents an existing topic on .Mac. The credentials set for this DMMessagePublisher instance will be used to access or modify the topic represented by the returned DMTopic object. To publish messages to a topic or to list the messages in a topic, a DMTopic object is required.

See also:

- 2.3.1 topicNamed(name as string) as DMTopicMBS 24
- 2.3.1 topicNamed(name as string, memberName as string) as DMTopicMBS 24

topics as DMTransactionMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Lists the topics that this DMMessagePublisher can publish messages to or remove messages from.

Notes: Each topic listed may be owned by this session's .Mac member credentials or by another .Mac member. Returns a DMTransaction object whose isSuccessful method can be used to test for success and

whose result method, upon success, returns an NSArray of all accessible DMTopic objects.

transactionDelegate as DMTransactionDelegateMBS

method from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

2.3.2 Properties

Handle as Integer

property from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.3.3 Constants

kDMInsufficientStorage=102

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac account does not have sufficient disk space to accommodate the given operation.

kDMInvalidCredentials=101

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac credentials set for this object do not have access to a .Mac account.

kDMNetworkError=103

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Unable to interact with .Mac because of a networking error or lack of network availability.

kDMResourceExists=105

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Indicates an error due to the pre-existence of a given resource.

kDMResourceNotFound=104

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: A required resource was not found.

kDMServiceBusy=106

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The given .Mac service was too busy to perform the requested operation and the operation should be retried later.

kDMSuccess=1

const from class DMMessagePublisherMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The operation was successful.

2.4 class DMTransactionMBS

class DMTransactionMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a transaction.

2.4.1 Methods

abort

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Stops the current transaction if it is running asynchronously, halting its progress.

Notes: If the transaction is already complete (or resulted in an error) this method has no effect.

bytesTransferred as Int64

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Most useful for asynchronous operations, this method returns the number of bytes downloaded or uploaded thus far.

contentLength as Int64

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the length in bytes of the content being downloaded or uploaded.

Notes: This returned length does not change over the life of the given transaction, except in the case where this method is called immediately after a GET request is started, before the content length has been received from the server this method returns kDMUndefined if called too early.

DictionaryResult as dictionary

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the result contains a dictionary.

Notes: Returns the result object of the given transaction as defined by the type of request the transaction is handling, if currently available and applicable. Otherwise returns nil.

errorType as integer

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The error type.

Notes: If an error occurred while generating the response associated with this object, this method will return a specific error type, as defined in the Constants section of this document. If an unknown error occurred, kDMUnknownError is returned. However, if no error occurred or the response has not yet completed when this method is called, kDMUndefined will be returned. [Note: If the http status code that was received is considered a failure code for the given transaction, kDMUnknownError is returned the http status code can be retrieved using the httpStatusCode method of this class.]

httpStatusCode as integer

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the HTTP status code for the request if applicable.

Notes:

Check RFC 2616 (HTTP/1.1) for a complete list of all of the applicable status codes. Some of the most noteworthy ones are:

- 200 Success
- 304 Not Modified
- 401 Authorization required
- 403 Forbidden. Your authorization credentials will not allow the transaction

attempted.

- 404 Not Found

[Note: kDMUndefined will be returned if the transaction has not yet completed, if an http status code is not applicable for the given transaction type, or if the transaction failed before an HTTP status code could even be received, as might be the case if the client computer could not contact the .Mac environment for some reason.]

IsDictionaryResult as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the result contains a dictionary.

isFinished as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether the transaction has finished.

Notes:

This method will return true if the given transaction is no longer active, due to success, error or cancellation. Otherwise, false is returned.

IsNumberResult as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the result contains a number.

IsStringArrayResult as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the result contains a string array.

IsStringResult as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the result contains a string.

isSuccessful as boolean

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether the transaction was successful.

Notes: Returns true if the transaction has finished successfully, no network errors occurred, and a valid http status code was returned. Otherwise, returns false.

NumberResult as double

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The result of this transaction as a number.

Notes: Returns the result object of the given transaction as defined by the type of request the transaction is handling, if currently available and applicable. Otherwise returns 0.

Result as variant

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The result as a variant.

Notes: Returns the result object of the given transaction as defined by the type of request the transaction is handling, if currently available and applicable. Otherwise returns nil.

StringArrayResult as string()

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The result of this transaction as a string array.

Notes: Returns the result object of the given transaction as defined by the type of request the transaction is handling, if currently available and applicable. Otherwise returns an empty array.

StringResult as string

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The result of the transaction as a string.

Notes: Returns the result object of the given transaction as defined by the type of request the transaction is handling, if currently available and applicable. Otherwise returns "".

transactionID as string

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a globally unique identifier string for this transaction.

transactionState as integer

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The state of this transaction.

Notes:

Returns one of the following integer constants:

Transaction State Constant	Meaning
kDMTransactionNotStarted	The transaction has not yet started.
kDMTransactionActive	The transaction is in progress.
kDMTransactionSuccessful	The transaction completed successfully and without error.
kDMTransactionAborted	DMTransactions abort method was called, halting the given transaction.
kDMTransactionHadError	A non-success http status code was returned, a network error occurred, or the expected data was not received. To get the exact error that occurred, call DMTransactions statusCode or errorType methods.

uri as string

method from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the target uri sent in this transactions originating request.

2.4.2 Properties

context as variant

property from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The context object set for this transaction.

Notes:

This value is nil by default.

Sets an object of the callers choosing on the given transaction that can be used to help identify a transaction. This method is especially useful in tracking transactions done asynchronously. After obtaining an asynchronously-fired DMTransaction object, the caller need not worry about the transaction completing and generating a delegate callback

before the context can be set—since callbacks are made on the same client thread which launched the transaction, setting the context simply needs to be done immediately after generating the transaction and in the same thread. That way, even if the transaction completes immediately, the context will still be set before the completion callback is made.

(Read and Write property)

Handle as Integer

property from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.4.3 Constants

kDMTransactionAborted=4

const from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the status constants returned by the DMTransactionMBS.transactionState method.

Notes: DMTransactions abort method was called, halting the given transaction.

kDMTransactionActive=2

const from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the status constants returned by the DMTransactionMBS.transactionState method.

Notes: The transaction is in progress.

kDMTransactionHadError=5

const from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the status constants returned by the DMTransactionMBS.transactionState method.

Notes: A non-success http status code was returned, a network error occurred, or the expected data was not received. To get the exact error that occurred, call DMTransactions statusCode or errorType methods.

kDMTransactionNotStarted=1

const from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the status constants returned by the DMTransactionMBS.transactionState method.

Notes: The transaction has not yet started.

kDMTransactionSuccessful=3

const from class DMTransactionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the status constants returned by the DMTransactionMBS.transactionState method.

Notes: The transaction completed successfully and without error.

2.5 Globals

LoadDotMacKitFrameworkMBS(path as folderitem) as boolean

global method, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Loads the DotMacKit framework from the given folderitem.

Example:

```
dim f as FolderItem = getfolderitem("DotMacKit.framework")

if LoadDotMacKitFrameworkMBS(f) then
  MsgBox "Framework loaded."
else
  MsgBox "Framework failed to load."
end if
```

Notes: Returns true on success and false on failure.

2.6 class DMTopicMBS

class DMTopicMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a topic.

Notes:

DMTopics have DMMessages published into them using a DMMessagePublisher session. Users of a DMMessageSubscriber session can subscribe to a DMTopic object in order to be informed when new messages are published to it. DMTopic objects can only be created using the factory methods of a DMMessagePublisher or a DMMessageSubscriber session, and they inherit the credentials of their parent message session. A topics namespace is scoped to its owner (the hosting .Mac member) and the application that created it.

A DMTopic object can be passed to DMSecurity protocol methods that take an 'entity' argument, in order to set access privileges on the given topic. When a .Mac member is granted access to a DMTopic, an invitation is automatically generated and can be accessed using a DMMessageSubscriber session.

2.6.1 Methods

applicationID as string

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the creator code of the application that created the topic.

credentials as DMMemberAccountMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the .Mac member object containing the credentials that will be used to access or modify this DMTopic object.

Notes: The returned credentials are the same credentials held by the DMMessagePublisher or DMMessageSubscriber instance that was used to get a reference to this DMTopic.

exists as DMTransactionMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The returned DMTransaction objects result method returns a Boolean value.

Notes: This value will be YES if the DMTopic exists and NO otherwise. [Note: If an error is encountered that prevents the existence check, the returned DMTransactions -errorType method can be used to identify the error.]

isAutoArrivalEnabledForMessagePayloads as boolean

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A boolean value indicating whether future messages received for the topic should have their payloads downloaded automatically to the local message cache

Notes:

This method sets whether future messages received for the topic should have their payloads downloaded automatically to the local message cache before any callbacks are made on a DMMessageSubscribers subscription delegate. When automatic downloading (or auto-arrival) of payloads is enabled, which is the default, a call to a DMMessages payload method simply returns the already-downloaded payload. When auto-arrival is not enabled for a given topic, a DMMessages payload method will do the extra work of downloading the payload on request. This method can be called regardless of whether a subscription to the given topic already exists. (A messages meta dataeverything but the payloadalways arrives automatically). [Note: Any auto-arrival default set by this method for a topic is automatically cleared from the local preferences cache if an unsubscribe call on the given topic is ever made in the future.] If this method is being called around the same time that a subscription to the given topic is being created, it is recommended that this method be called first, before the call to DMMessageSubscribers subscribeToTopic method. This ensures that the desired auto-arrival behavior is in place for the given topic before any topic-related callbacks are made into a DMMessageSubscribers subscription delegate.

This method returns a boolean value indicating whether future messages received for the topic should have their payloads downloaded automatically to the local message cache before any callbacks are made on a DMMessageSubscribers subscription delegate. When automatic downloading (or auto-arrival) of payloads is enabled, which is the default, a call to a DMMessages payload method simply returns the already-downloaded payload. When auto-arrival is not enabled for a given topic, a DMMessages -payload method will do the extra work of downloading the payload on request.
(Read and Write computed property)

isSynchronous as boolean

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]
(Read and Write computed property)

messages as DMMessageMBS()

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns all DMMessages found in this DMTopic on .Mac, as an NSArray of DMMessages.

Notes: Messages are ordered by publication time, starting with the earliest.

messageWithID(messageID as string) as DMMessageMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Retrieves a DMMessage using its globally unique identifier.

Notes: Returns a DMMessage if the provided message identifier is valid, and nil otherwise.

name as string

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the topic.

newestMessage as DMMessageMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the most recent DMMessage in the topic, based on publication time.

newMessages as DMMessageMBS()

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns all DMMessages in this DMTopic that have not yet been accessed by the caller.

Notes: (The caller is defined as a combination of the .Mac credentials set for the session that created this DMTopic, the machine and local OS X user that the calling application is running under and the calling application itself.) This method will most often be called after a DMMessageSubscriber sessions subscription delegate is informed of a change in this DMTopic. Returns an NSArray of DMMessages ordered by publication time, starting with the earliest.

oldestMessage as DMMessageMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the oldest DMMessage in the topic, based on publication time.

owner as string

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the .Mac member who owns and hosts the topic.

removeMessages as DMTransactionMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes all DMMessages from this DMTopic on .Mac.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success. This method can only be called if the .Mac credentials being used have write access to the given topic.

removeMessageWithID(messageID as string) as DMTransactionMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes the identified DMMessage from this DMTopic on .Mac.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success. This method can only be called if the .Mac credentials being used have write access to the given topic.

resetTimeToLive(ttl as double, messageID as string) as DMTransactionMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Resets the time-to-live value of the DMMessage specified by given identifier.

Notes: Returns a DMTransaction object whose -isSuccessful method can be used to test for success. The provided time-to-live value, an NSTimeInterval with precision in seconds, cannot be greater than 30 days. This method can only be called if the .Mac credentials being used have write access to the given topic.

transactionDelegate as DMTransactionDelegateMBS

method from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous trans-

actions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

2.6.2 Properties

Handle as Integer

property from class DMTopicMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.7 class DMTransactionDelegateMBS

class DMTransactionDelegateMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for getting transaction events.

2.7.1 Methods

Constructor

method from class DMTransactionDelegateMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The constructor to create a new object.

2.7.2 Properties

Handle as Integer

property from class DMTransactionDelegateMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.7.3 Events

transactionAborted(Transaction as DMTransactionMBS)

event from class DMTransactionDelegateMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This delegate method is called after the DMTransaction objects abort method is called and stops a currently-running asynchronous transaction.

transactionHadError(Transaction as DMTransactionMBS)

event from class DMTransactionDelegateMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This delegate method is called when a transaction encounters an error condition.

Notes: If the transaction does complete successfully, then transactionSuccessful: is called instead. Takes one parameter, which is a reference to the DMTransaction object that experienced the error.

transactionSuccessful(Transaction as DMTransactionMBS)

event from class DMTransactionDelegateMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This delegate method is called when a transaction successfully completes.

Notes: If the transaction does not complete successfully, then `transactionHadError:` is called instead. Takes one parameter, which is a reference to the DMTransaction object that completed.

2.8 class DMGroupMBS

class DMGroupMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a group.

2.8.1 Methods

addMembers(members() as string) as DMTransactionMBS

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Adds members to the given .Mac member-owned group.

Notes: If the group already exists, then the identified principals are added as members. If the group does not already exist, this call fails. The `members` argument is an NSArray of principal ID strings that identify principals corresponding to DMMemberAccounts, DMSecondaryUsers and/or other DMGroup objects. Returns a DMTransaction object whose `-isSuccessful` method can be used to test for success.

isSynchronous as boolean

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]
(Read and Write computed property)

members as DMTransactionMBS

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Lists all members of the given .Mac member-owned group.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success and whose -result method, upon success, returns an Array of principal ID strings that identify principals corresponding to DMMemberAccounts, DMSecondaryUsers and/or other DMGroup objects.

name as string

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the .Mac member-owned group represented by this DMGroup object.

owner as string

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the .Mac member who owns this group.

principalID as string

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method is implemented by DMMemberAccount, DMSecondaryUser or DMGroup and returns the appropriate principal ID string.

principalIDWithName(name as string, memberName as string) as string

shared method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a principal ID string identifying the principal with the given name and owner (the owner is the name of the .Mac member that owns the given principal).

Notes: This class method is useful when the caller needs to obtain a principle ID representing a DMMemberAccount, DMSecondaryUser or DMGroup without creating an instance of one of those classes.

removeMembers(members() as string) as DMTransactionMBS

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes members from the given .Mac member-owned group.

Notes: The members argument is an NSArray of principal ID strings that identify principals corresponding to DMMemberAccounts, DMSecondaryUsers and/or other DMGroup objects. Returns a DMTransaction object whose -isSuccessful method can be used to test for success.

transactionDelegate as DMTransactionDelegateMBS

method from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

2.8.2 Properties**Handle as Integer**

property from class DMGroupMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.9 class DMiDiskSessionMBS**class DMiDiskSessionMBS**

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for an iDisk Session.

Notes: Please note: All server-side paths passed as arguments to DMiDiskFileManager category methods should start with a forward slash, omitting the iDisk account name at the beginning of the path for example, if uploading a local file to a users Public folder, the path passed to the createFileAtPath method would be

of the format `/Public/<filename>`.

2.9.1 Methods

account as DMAccountMBS

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The account used for this session.

basicAttributesAtPath(path as string) as DMTransactionMBS

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Performs a lightweight access against a single file or collection (directory) resource referenced by `thePath`.

Notes:

Use this method when only basic information such as the last modified date or content length is needed, as it is lighter weight than an `extendedAttributesAtPath` call. If a resource exists at `thePath` and the transaction is successful, the returned `DMTransaction` objects result method returns an `NSDictionary`. That `NSDictionary` contains resource attributes whose values, if present and applicable, can be retrieved using the following `NSString` key constants:

Key	Corresponding Value Type
<code>kDMContentLength</code>	Number (bytes)
<code>kDMLastModified</code>	Date

[Note: `kDMContentLength` is not returned for collections.] Returns a `DMTransaction` object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

Constructor(c as DMAccountMBS) as DMiDiskSessionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMSecondaryUserMBS object. The session will be used to access the iDisk owned by the .Mac member with the given credentials.

See also:

- 2.9.1 Constructor(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS 49
- 2.9.1 Constructor(c as DMSecondaryUserMBS) as DMiDiskSessionMBS 49
- 2.9.1 Constructor(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS 50

Constructor(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMSecondaryUserMBS object and also takes the name of the .Mac member whose iDisk is to be accessed using the provided credentials.

See also:

- 2.9.1 Constructor(c as DMAccountMBS) as DMiDiskSessionMBS 49
- 2.9.1 Constructor(c as DMSecondaryUserMBS) as DMiDiskSessionMBS 49
- 2.9.1 Constructor(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS 50

Constructor(c as DMSecondaryUserMBS) as DMiDiskSessionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMSecondaryUserMBS object. The session will be used to access the iDisk owned by

the `.Mac` member with the given credentials.

See also:

- 2.9.1 Constructor(`c` as `DMAccountMBS`) as `DMiDiskSessionMBS` 49
- 2.9.1 Constructor(`c` as `DMAccountMBS`, `memberName` as string) as `DMiDiskSessionMBS` 49
- 2.9.1 Constructor(`c` as `DMSecondaryUserMBS`, `memberName` as string) as `DMiDiskSessionMBS` 50

Constructor(`c` as `DMSecondaryUserMBS`, `memberName` as string) as `DMiDiskSessionMBS`

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the `.Mac` iDisk servers.

Notes: It takes an `DMSecondaryUserMBS` object and also takes the name of the `.Mac` member whose iDisk is to be accessed using the provided credentials.

See also:

- 2.9.1 Constructor(`c` as `DMAccountMBS`) as `DMiDiskSessionMBS` 49
- 2.9.1 Constructor(`c` as `DMAccountMBS`, `memberName` as string) as `DMiDiskSessionMBS` 49
- 2.9.1 Constructor(`c` as `DMSecondaryUserMBS`) as `DMiDiskSessionMBS` 49

contentsAtPath(`path` as string) as string

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the contents of the remote file specified in `path` as a string.

Notes: If `path` specifies a directory, or if some other error occurs, this method returns `nil`. [Note: Only the data fork of the given file is returned.]

copyPath(`source` as string, `destination` as string) as boolean

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will create a copy of the source resource at the given destination path, but will not overwrite an existing resource.

Notes:

Each path argument can be either a local or a remote path. Passing a local source path and remote destination path leads to an upload of a local resource, while passing a remote source path and local destination path leads to a download of a remote resource. If two remote paths are provided as arguments, this method issues a single, server-side COPY request. This method has usage similar to that of the corresponding method of `NSFileManager`. However, it does not support the usage of a callback handler and if a non-nil handler argument is passed to this method, it will be ignored. In the case of an upload or download, only the data forks of files and directories are copied. In the case of an upload, local symlinks are not preserved. When a symlink is encountered, the resource it references will be uploaded. [Note: If two local paths are provided as arguments, this method calls `NSFileManagers copyPath` method with whatever handler argument was provided.]

For the plugin the `handle` parameter is always nil.

copyResourceAtPath(sourcePath as string, destinationPath as string) as DMTransactionMBS

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Copies the resource identified by `sourcePath` if the account who owns the credentials used has write access to `destinationPath`.

Notes: This method will overwrite the resource at `destinationPath` if that resource is not locked by another client. Returns a `DMTransaction` object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

createDirectoryAtPath(path as string) as boolean

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will create a new directory at the given remote path.

Notes: It has the same usage as the corresponding method of `NSFileManager`. However, it does not support the setting of attributes and if a non-nil attributes argument is passed to this method, it will be ignored.

createFilePath(path as string, content as string) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates a remote file at path that contains contents, behavior which matches the style of the corresponding method of NSFileManager.

Notes: However, it does not support the setting of attributes and if a non-nil attributes argument is passed to this method, it will be ignored.

credentials as variant

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the DMCredential-conforming object containing the credentials used to access this sessions iDisk.

Notes: Returns a DMAccountMBS or a DMSecondaryUserMBS object.

defaultLockDuration as double

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The default lock duration set for this DMiDiskSession instance.

Notes:

Returns the default lock duration set for this DMiDiskSession instance. If no default lock duration has been set for this instance using the setDefaultLockDuration: method, an NSTimeInterval representing 5 minutes, given in seconds, is returned.

This method sets the default lock duration, in seconds, used by all lock-related DMiDiskSession methods that do not specify a transaction-specific lock duration of their own. If this method is not called, the default lock duration is 5 minutes, given in seconds.

(Read and Write computed property)

deleteResourceAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Deletes the resource referenced by thePath if it is not locked by another client and the account who owns the credentials used has write access to thePath.

Notes:

If the delete request fails because the specified resource or its parent is locked, the returned DMTransaction objects result method will return an Array of Strings representing the exact uris which are currently locked. [Note: Unlike on most file systems, a non-empty collection (directory) can be deleted. Issuing a delete targeted at a collection will delete the collection and all of its contents without warning (assuming you have the correct access privileges).] Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

directoryContentsAtPath(Path as string) as string()

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Searches the contents of the remote directory specified by path and returns an array of strings identifying the directories and files (including symbolic links) contained in path.

Notes: The search is shallow and therefore does not return the contents of any subdirectories. Returns nil if the directory specified at path does not exist or there is some other error accessing it. Returns an empty array if the directory exists but has no contents.

extendedAttributesAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method provides the attributes of the file or collection (directory) resource specified by thePath.

Notes:

If a resource exists at thePath and the request is successful, the returned DMTransaction objects result method returns an NSDictionary. That NSDictionary contains resource attributes whose values, if present and applicable, can be retrieved using the following NSString key constants:

Key	Corresponding Value Type
kDMContentLength	Number (bytes)
kDMLastModified	Date
kDMURI	String
kDMDisplayName	String
kDMContentType	String
kDMIsCollection	Number (Boolean)
kDMIsLocked	Number (Boolean)
kDMLockOwner	String
kDMLockToken	String
kDMLockTimeout	Number (seconds)

[Note: kDMContentLength is not returned for collections.] Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

fileExistsAtPath(path as string) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns YES if the remote file specified in path exists, or NO if it does not.
See also:

- 2.9.1 fileExistsAtPath(path as string, byref isDirectory as boolean) as boolean 54

fileExistsAtPath(path as string, byref isDirectory as boolean) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns whether the remote file specified in path exists.

Notes: If you want to determine if path is a directory, specify the address of a Boolean variable for isDirectory, which will be set to YES if path is a directory, and to NO otherwise.
See also:

- 2.9.1 fileExistsAtPath(path as string) as boolean 54

getDataAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Loads data from a given path.

Notes: If the transaction is successful, the returned DMTransaction objects result method returns a string containing the desired resource. [Note: If the transaction is not yet complete, the result method will return the data that has been downloaded so far.] The returned DMTransaction object can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction. See also:

- 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date) as DMTransactionMBS 55
- 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date, ByteStart as double, ByteLength as double) as DMTransactionMBS 55

getDataAtPath(sourcePath as string, IfModifiedSince as date) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Loads data from a given path.

Notes: If the transaction is successful, the returned DMTransaction objects result method returns a string containing the desired resource. [Note: If the transaction is asynchronous and is not yet complete, the result method will return the data that has been downloaded so far.] The returned DMTransaction object can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 getDataAtPath(path as string) as DMTransactionMBS 55
- 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date, ByteStart as double, ByteLength as double) as DMTransactionMBS 55

getDataAtPath(sourcePath as string, IfModifiedSince as date, ByteStart as double, ByteLength as double) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Loads data from a given path.

Notes: If the transaction is successful, the returned DMTransaction object's result method returns a string containing the desired resource. The NSRange object, passed as the byteRange argument, should have its location set as the index of the first byte to be retrieved and its length should be set as the total number of bytes to be retrieved, including the first byte. You can also pass nil for lastModifiedDate if you are not interested in when the server resource was last modified. [Note: If the transaction is asynchronous and is not yet complete, the result method will return the data that has been downloaded so far.] The returned DMTransaction object can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 getDataAtPath(path as string) as DMTransactionMBS 55
- 2.9.1 getDataAtPath(sourcePath as string, IfModifiedSince as date) as DMTransactionMBS 55

iDiskSessionWithCredentials(c as DMAccountMBS) as DMiDiskSessionMBS

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMAccountMBS object. The returned session will be used to access the iDisk owned by the .Mac member with the given credentials.

See also:

- 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS 56
- 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS) as DMiDiskSessionMBS 57
- 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS 57

iDiskSessionWithCredentials(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMAccountMBS object and also takes the name of the .Mac member whose iDisk is to be accessed using the provided credentials.

See also:

- 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS) as DMiDiskSessionMBS 56
- 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS) as DMiDiskSessionMBS 57
- 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS 57

iDiskSessionWithCredentials(c as DMSecondaryUserMBS) as DMiDiskSessionMBS

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMSecondaryUserMBS object. The returned session will be used to access the iDisk owned by the .Mac member with the given credentials.

See also:

- 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS) as DMiDiskSessionMBS 56
- 2.9.1 iDiskSessionWithCredentials(c as DMAccountMBS, memberName as string) as DMiDiskSessionMBS 56
- 2.9.1 iDiskSessionWithCredentials(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS 57

iDiskSessionWithCredentials(c as DMSecondaryUserMBS, memberName as string) as DMiDiskSessionMBS

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates an iDisk session instance that can be used to perform I/O transactions with the .Mac iDisk servers.

Notes: It takes an DMSecondaryUserMBS object and also takes the name of the .Mac member whose iDisk is to be accessed using the provided credentials.

See also:

- 2.9.1 `iDiskSessionWithCredentials(c as DMAccountMBS)` as `DMiDiskSessionMBS` 56
- 2.9.1 `iDiskSessionWithCredentials(c as DMAccountMBS, memberName as string)` as `DMiDiskSessionMBS` 56
- 2.9.1 `iDiskSessionWithCredentials(c as DMSecondaryUserMBS)` as `DMiDiskSessionMBS` 57

isSynchronous as boolean

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a `DMTransaction` object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight `DMTransaction` object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]

(Read and Write computed property)

kDMModify as string

shared method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes modify access to a given entity. Does not include create or delete access.

kDMRead as string

shared method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does

nothing.

Function: One of the privileges constants.

Notes: Includes read and list access to a given entity.

kDMReadChildren as string

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes read and list access to children of a given entity only. Does not include read and list access to the entity itself.

kDMWrite as string

shared method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the privileges constants.

Notes: Includes create, modify and delete access to a given entity.

listCollectionAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Lists the collection at the given path.

lockResourceAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Locks the resource referenced by thePath so that only this session can execute write operations (e.g., PUT, DELETE) on that resource.

Notes:

The iDisk server reserves the right to grant a lock duration/timeout that differs from the requested lock duration when this method is successful, the returned DMTransaction objects result method will return an NSDictionary containing an NSNumber value (accessible using the kDMLockTimeout key) which is the lock timeout that was granted by the server. The lock will expire after the time specified by the granted lock timeout (in seconds) has passed. If the lock request fails because the specified resource or its parent is already locked, the returned DMTransaction objects result method will return an NSArray of NSStrings representing the exact uris which are currently locked. To maintain a lock, issue a relock request on the same resource before the original lock has expired. [Note: The lock created is a cooperative, write lock.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 lockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS 60

lockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Locks the resource referenced by thePath so that only this session can execute write operations (e.g., PUT, DELETE) on that resource.

Notes:

The iDisk server reserves the right to grant a lock duration/timeout that differs from the requested lock duration when this method is successful, the returned DMTransaction objects result method will return an NSDictionary containing an NSNumber value (accessible using the kDMLockTimeout key) which is the lock timeout that was granted by the server. The lock will expire after the time specified by the granted lock timeout (in seconds) has passed. If the lock request fails because the specified resource or its parent is already locked, the returned DMTransaction objects result method will return an NSArray of NSStrings representing the exact uris which are currently locked. To maintain a lock, issue a relock request on the same resource before the original lock has expired. [Note: The lock created is a cooperative, write lock.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 lockResourceAtPath(path as string) as DMTransactionMBS 59

makeCollectionAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method creates a collection (directory) at the location specified in thePath.

Notes: If any of the levels above the one being created does not exist, then the create will fail. Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

movePath(source as string, destination as string) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will move the source resource to the given destination path, but will not overwrite an existing resource.

Notes:

Each path argument can be either a local or a remote path. Passing a local source path and remote destination path leads to an upload of a local resource, while passing a remote source path and local destination path leads to a download of a remote resource. If two remote paths are provided as arguments, this method issues a single, server-side MOVE request. This method has usage similar to that of the corresponding method of NSFileManager. However, it does not support the usage of a callback handler and if a non-nil handler argument is passed to this method, it will be ignored. In the case of an upload or download, only the data forks of files and directories are moved. In the case of an upload, local symlinks are not preserved. When a symlink is encountered, the resource it references will be uploaded. [Note: If two local paths are provided as arguments, this method calls NSManagers movePath method with whatever handler argument was provided.]

For the plugin the handle parameter is always nil.

moveResourceAtPath(sourcePath as string, destinationPath as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Moves the resource identified by sourcePath if it is not locked by another client and the account who owns the credentials used has write access to destinationPath.

Notes:

This method will overwrite the resource at `destinationPath` if that resource is not locked by another client. Returns a `DMTransaction` object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

owner as string

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the `.Mac` member who owns the `iDisk` being accessed by this session.

putData(data as string, destinationPath as string) as DMTransactionMBS

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method places the contents of the `data` argument into the resource at the location specified by the `destinationPath`.

Notes:

[Note: Call will fail if any sublevels of `destinationPath` (excluding the object itself) do not exist, and the call may return `nil` if an invalid `data` argument is passed.]

Returns a `DMTransaction` object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 `putData(data as string, destinationPath as string, ByteStart as double, ByteLength as double) as DMTransactionMBS` 62

putData(data as string, destinationPath as string, ByteStart as double, ByteLength as double) as DMTransactionMBS

method from class `DMiDiskSessionMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method places the contents of the `data` argument into the resource at the location specified by the `byteRange` argument.

Notes:

The NSRange object, passed as the byteRange argument, should have its location set as the index of the first byte to be written to and its length should be set as the total number of bytes, including the first byte. If the end of the specified range is beyond the end of the file, then the length of the resource is extended to accommodate all of the bytes. [Note: Call will fail if any sublevels of destinationPath (excluding the object itself) do not exist, and the call may return nil if an invalid data argument is passed.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 putData(data as string, destinationPath as string) as DMTransactionMBS

62

putLocalFileAtPath(localPath as string, destinationPath as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method places the contents of a local file into a new server-side file at the given destination path.

Notes:

If the localPath parameter refers to a symlink, the symlink will not be preserved rather, the resource it references will be uploaded. [Note: Call will fail if all sublevels of destinationPath (excluding the object itself) do not already exist, and the call may return nil if an invalid localPath argument is passed.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

quotaAttributes as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Use this method to get the users iDisk quota value along with the amount of storage space that is currently used.

Notes:

The returned DMTransaction objects result method returns an Dictionary containing two Number values, which can be retrieved using the following key constants:

Key Constant	Corresponding Value Type
kDMiDiskQuotaInBytes	Number (bytes)
kDMiDiskSpaceUsedInBytes	Number (bytes)

relockResourceAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Refreshes the lock on the resource referenced by thePath.

Notes:

The iDisk server reserves the right to grant a lock duration/timeout that differs from the requested lock duration when this method is successful, the returned DMTransaction objects result method will return an Dictionary containing an NSNumber value (accessible using the kDMLockTimeout key) which is the lock timeout that was granted by the server. Once refreshed, the lock will expire after the time specified by the granted lock timeout (in seconds) has passed. Attempting to relock a resource that is not locked will always fail. If the relock request fails because the specified resource or its parent was originally locked by another client, the returned DMTransaction objects result method will return an array of Strings representing the exact uris which are currently locked. [Note: The lock created is a cooperative, write lock.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

See also:

- 2.9.1 relockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS 64

relockResourceAtPath(Path as string, lockDuration as double) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Refreshes the lock on the resource referenced by thePath.

Notes:

The iDisk server reserves the right to grant a lock duration/timeout that differs from the requested lock duration when this method is successful, the returned DMTransaction objects result method will return an NSDictionary containing an NSNumber value (accessible using the kDMLockTimeout key) which is the lock timeout that was granted by the server. Once refreshed, the lock will expire after the time specified by the granted lock timeout (in seconds) has passed. Attempting to relock a resource that is not locked will always fail. If the relock request fails because the specified resource or its parent was originally locked by another client, the returned DMTransaction objects result method will return an NSArray of NSStrings representing the exact uris which are currently locked. [Note: The lock created is a cooperative, write lock.]

Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and

many other pieces of information about the actual transaction.
See also:

- 2.9.1 relockResourceAtPath(path as string) as DMTransactionMBS

64

removeFileAtPath(path as string) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will remove the resource at the given remote path and has the same usage as the corresponding method of NSFileManager.

Notes: However, it does not support the usage of a callback handler and if a non-nil handler argument is passed to this method, it will be ignored.

resourceExistsAtPath(path as string) as boolean

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A method which always operates synchronously, resourceExistsAtPath returns true if the resource specified by thePath exists on the iDisk server, and returns false otherwise.

Notes: [Note: To check for the existence of a resource asynchronously, use the basicAttributesAtPath: method.]

transactionDelegate as DMTransactionDelegateMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that

were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

unlockResourceAtPath(path as string) as DMTransactionMBS

method from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Releases any lock on the resource referenced by thePath.

Notes: Attempting to unlock a resource that is not locked will fail. Returns a DMTransaction object that can be used to get the result of the transaction, status, payload, and many other pieces of information about the actual transaction.

2.9.2 Properties

Handle as Integer

property from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.9.3 Constants

kDMContentLength = "DAV:getcontentlength"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSessionMBS.extendedAttributesAtPath or DMiDiskSessionMBS.basicAttributesAtPath.

Notes: Value is a number.

kDMContentType = "DAV:getcontenttype"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a string.

kDMDateCreated = "DAV:creationdate"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit constants.

kDMDebugLogging = "DMDebugLogging"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit constants.

kDMDisplayName = "DAV:displayname"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit constants.

kDMErrorLogging = "DMErrorLogging"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit constants.

kDMGroup = "Group"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the principal type constants.

Notes: Type for principal representing a .Mac member-owned group.

kDMiDiskQuotaInBytes = "DAV:quota"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the dictionary keys in the dictionary returned from DMiDiskSession.quotaAttributes

Notes: A number with the bytes.

kDMiDiskSpaceUsedInBytes = "DAV:quotaused"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the dictionary keys in the dictionary returned from DMiDiskSession.quotaAttributes

Notes: A number with the bytes.

kDMIsCollection = "IsCollection"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a boolean.

kDMIIsLocked = "IsLocked"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a boolean.

kDMLastModified = "DAV:getlastmodified"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSessionMBS.extendedAttributesAtPath or DMiDiskSessionMBS.basicAttributesAtPath.

Notes: Value is a date.

kDMLockOwner = "LockOwner"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a string.

kDMLockTimeout = "LockTimeout"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a number (seconds).

kDMLockToken = "LockToken"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit),
Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a string.

kDMLoggingLevel = "com.apple.DotMacKit.LoggingLevel"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit),
Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit constants.

kDMMemberAccount = ".Mac Member"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit),
Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the principal type constants.

Notes: Type for principal representing .Mac member.

kDMPrincipalName = "PrincipalName"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit),
Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants for principalPropertiesFromPrincipalID.

Notes: The name of the given principal.

kDMPrincipalOwner = "PrincipalOwner"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants for principalPropertiesFromPrincipalID.

Notes: The name of the .Mac member who owns the principal—this is the same as the principal name if the principal represents a DMMemberAccount.

kDMPrincipalType = "PrincipalType"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants for principalPropertiesFromPrincipalID.

Notes: The type of the given principal, which is one of the Principal Type Constants listed below.

kDMSecondaryUser = "Secondary User"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the principal type constants.

Notes: Type for principal representing a .Mac member-owned secondary user.

kDMURI = "URI"

const from class DMiDiskSessionMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the constants used as key in the dictionary you get from DMiDiskSession.extendedAttributesAtPath.

Notes: Value is a string.

2.10 class DMAccountMBS

class DMAccountMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for an account.

2.10.1 Methods

applicationID as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The application ID currently set for this DMMemberAccount object is returned.

Notes: (Read and Write computed property)

applicationName as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The human-readable name of the calling application is returned if set.

Notes:

This method sets the human-readable name of the calling application. Once set, it will be included in the user-agent header sent with all http requests.

(Read and Write computed property)

name as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A username string is returned.

owner as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The name of the .Mac member who owns the credential is returned.

password as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: A password string is returned.

principalID as string

method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method is implemented by DMMemberAccount, DMSecondaryUser or DMGroup and returns the appropriate principal ID string.

principalIDWithName(name as string, memberName as string) as string

shared method from class DMAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns a principal ID string identifying the principal with the given name and owner (the owner is the name of the .Mac member that owns the given principal).

Notes: This class method is useful when the caller needs to obtain a principle ID representing a DMMemberAccount, DMSecondaryUser or DMGroup without creating an instance of one of those classes.

2.10.2 Properties

Handle as Integer

property from class `DMAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.11 class `DMMMessageMBS`

class `DMMMessageMBS`

class, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a message.

Notes: Once published to a `DMTopic`, a `DMMMessage` object becomes immutable. Use `DMMessages.isPublished` method to determine whether a message has been published to `.Mac`.

2.11.1 Methods

`Constructor(messageString as string)`

method from class `DMMMessageMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates a newly initialized `DMMMessage` instance containing the provided message string.

Notes: This is a convenience method for creating a `DMMMessage` containing just the provided message string and no payload object or properties dictionary. The message string cannot exceed 1K in size.

expirationDate as date

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: If this DMMessage has already been published, this method returns an NSDate that marks the time this DMMessage expires (with precision in seconds).

Notes: Otherwise, this method returns nil. If the expiration time returned for this DMMessage is in the past, it means that this message is awaiting clean-up.

isPublished as boolean

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Tells whether the DMMessage has already been published to .Mac.

Notes: A DMMessage can be published to .Mac only once and it becomes immutable once published. An attempt to publish a DMMessage more than once will fail. Returns a BOOL value.

isSynchronous as boolean

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]

(Read and Write computed property)

messageID as string

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns this DMMessage's globally unique identifier string.

messageString as string

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the optional message string set for the DMMessage.

payload as DMTransactionMBS

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Retrieves the optional payload object set for the DMMessage.

Notes: Upon success, the returned DMTransaction objects result method will return this messages payload object, an object that conforms to the NSCodering protocol. If auto-arrival of payloads is enabled for this messages parent topic, then the payload object is already available locally by the time this new message is received and the caller can call the returned DMTransactions -result method right away. However, if auto-arrival is disabled, this DMMessages payload is not downloaded until this -payload method is called. If this DMMessages transaction processing is set to asynchronous, then the status of the download can be observed by setting this DMMessages transaction delegate or through polling the returned DMTransaction object. [Note: If this DMMessages transaction delegate is not set, then it will inherit any transaction delegate that is explicitly set for its parent DMTopic or that has been inherited by its parent DMTopic from the session object used to create it.] If auto-arrival is disabled and this DMMessages transaction processing is set to synchronous, then this method will not return until the payload is completely downloaded. In all cases, the payload is retrieved with a call to the returned DMTransaction objects -result method.

payloadType as string

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the type corresponding to the payload for this DMMessage.

Notes: The payload type is an NSString that represents the file type that would be used if the payload object were serialized to disk. Returns a type string, or nil if no payload object is set for this DMMessage.

properties as dictionary

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the optional user-defined properties dictionary set for this DMMessage.

publicationDate as date

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the time when this DMMessage was published to .Mac, which is an NSDate object with precision in seconds.

Notes: If this DMMessage has not yet been published, this method returns nil.

publisher as string

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the name of the .Mac member who published this DMMessage to .Mac.

Notes: Returns "" if this DMMessage has not yet been published.

setMessageString(messageString as string) as integer

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Sets the optional message string for the DMMessage.

Notes: The message string cannot exceed 1K in size. An integer status constant is returned. [Note: Calling

this method on an already-published message will result in `kDMResourceExists` being returned; otherwise, this method returns `kDMSuccess`. The `-isPublished` method can be used to determine whether this `DMMessage` has already been published.]

setProperty(dic as dictionary) as integer

method from class `DMMessageMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Sets the optional properties dictionary for this `DMMessage`.

Notes: This dictionary cannot exceed 100K in size. The dictionary can contain `NSString` keys and values only and the 100K limit includes both keys and values. [Note: Calling this method on an already-published message will result in `kDMResourceExists` being returned; otherwise, this method returns `kDMSuccess`. The `isPublished` method can be used to determine whether this `DMMessage` has already been published.]

setTimeToLive(timeToLive as double) as integer

method from class `DMMessageMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method can be used to set the time-to-live for this `DMMessage` prior to publication.

Notes:

The default time-to-live is 7 days, and the time-to-live cannot be made longer than 30 days. Takes an `NSTimeInterval` (precision in seconds). [Note: Calling this method on an already-published message will result in `kDMResourceExists` being returned; otherwise, this method returns `kDMSuccess`. The `-isPublished` method can be used to determine whether this `DMMessage` has already been published.]

(Read and Write computed property)

timeToLive as double

method from class `DMMessageMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The time to live for this message.

Notes:

Returns an `NSTimeInterval` (with precision in seconds) representing the default time-to-live of 7 days if the

default was not overridden by a DMMessagePublisher setting or by a call to this DMMessage setTimeToLive method.

(Read and Write computed property)

topic as DMTopicMBS

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the topic that contains this DMMessage.

Notes: Returns nil if this DMMessage has not yet been published to a topic.

transactionDelegate as DMTransactionDelegateMBS

method from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

2.11.2 Properties

Handle as Integer

property from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The internal object reference.

Notes: (Read and Write property)

2.11.3 Constants

kDMInsufficientStorage=102

const from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac account does not have sufficient disk space to accommodate the given operation.

kDMInvalidCredentials=101

const from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac credentials set for this object do not have access to a .Mac account.

kDMNetworkError=103

const from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Unable to interact with .Mac because of a networking error or lack of network availability.

kDMResourceExists=105

const from class DMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Indicates an error due to the pre-existence of a given resource.

kDMResourceNotFound=104

const from class DMMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: A required resource was not found.

kDMServiceBusy=106

const from class DMMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The given .Mac service was too busy to perform the requested operation and the operation should be retried later.

kDMSuccess=1

const from class DMMMessageMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The operation was successful.

2.12 class DMMemberAccountMBS

class DMMemberAccountMBS

class, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The class for a member account.

Notes: Subclass of the DMAccountMBS class.

2.12.1 Methods

accountFromPreferencesWithApplicationID(creatorCode as string) as DMMemberAccountMBS

shared method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an initialized instance of DMMemberAccount keyed to a specific applications identification string.

Notes:

The instance returned will have the .Mac name and password from the system pre-applied. Pass the unique 4-character application identifier obtained from <http://developer.apple.com/datatype/creatorcode.html>.

accountUpgradeURL as string

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method provides access to the same localized URL that the upgradeAccount method loads in the default browser.

accountWithName(name as string, password as string, creatorCode as string) as DMMemberAccountMBS

shared method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns an initialized instance of DMMemberAccount keyed to a specific applications identification string.

Notes:

The instance returned will use the provided name and password, rather than any credentials stored in the .Mac preferences on the system. (To have the credentials stored on the system pre-applied, use the `accountFromPreferencesWithApplicationID:` method instead.) Pass the unique 4- character application identifier obtained from <http://developer.apple.com/datatype/creatorcode.html>.

canUpgradeAccount as DMTransactionMBS

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether this account can be upgraded.

Notes: The returned `DMTransaction` objects result method returns a Boolean value. This value will be YES if the `DMMemberAccount` objects credentials are associated with an existing account that can be upgraded, such as a trial or email-only account, or if the account has expired and needs to be renewed. Otherwise, the resulting value will be NO. [Note: If the account credentials do not exist or some other error occurs, the returned `DMTransactions` `errorType` method can be used to identify the error.]

Constructor(creatorCode as string)

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates an instance of `DMMemberAccount` keyed to a specific applications identification string.

Notes:

The instance returned will have the .Mac name and password from the system pre-applied. Pass the unique application identifying string obtained from

<http://developer.apple.com/datatype/creatorcode.html>

See also:

- 2.12.1 `Constructor(name as string, password as string, creatorCode as string)`

Constructor(name as string, password as string, creatorCode as string)

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Creates an initialized instance of `DMMemberAccount` keyed to a specific applications identification string.

Notes:

The instance returned will use the provided name and password, rather than any credentials stored in the `.Mac` preferences on the system. (To have the credentials stored on the system pre-applied, use the `initWithPreferencesWithApplicationID:` method instead.) Pass the unique application identifying string obtained from

<http://developer.apple.com/datatype/creatorcode.html>

See also:

- 2.12.1 `Constructor(creatorCode as string)`

83

`createGroupWithName(name as string, members() as string) as DMTransactionMBS`

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method can be used to create a new `DMGroup` object with the provided name and members if a group of the same name does not already exist for the owners account on `.Mac`.

Notes: The `members` argument is an Array of principal ID strings identifying principals corresponding to `DMMemberAccounts`, `DMSecondaryUsers` and/or `DMGroup` objects. Returns a `DMTransaction` object whose `isSuccessful` method can be used to test for success.

`createSecondaryUserWithName(name as string, password as string) as DMTransactionMBS`

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Adds a secondary user to `.Mac` if a secondary user of the same name does not already exist for this owning member account.

Notes: Returns a `DMTransaction` object whose `isSuccessful` method can be used to test for success.

daysLeftUntilExpiration as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The returned DMTransaction objects result method returns a number representing the number of full days left until the given account expires.

Notes: [Note: If the account credentials do not exist or some other error occurs, the returned DMTransactions errorType method can be used to identify the error.]

groupNamed(name as string) as DMGroupMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Use this method to obtain a DMGroup object representing a known group that already exists.

groupNames as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Lists all groups owned by this .Mac member.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success and whose result method returns an Array of String group names upon success.

isSynchronous as boolean

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Whether transactions are performed synchronous (true) or asynchronous (false).

Notes:

The default mode is asynchronous.

This property is used to set the synchronicity state for generated transactions. Passing true will cause the object's transaction methods to block until they have either completed their transaction or failed with an error. Passing false will cause the methods to that return a DMTransaction object to return immediately, using any previously set delegate object to signal completion or error. It is safe to call this method to switch between asynchronous and synchronous modes as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. [Note: The default mode is asynchronous.]

(Read and Write computed property)

matchesSystemCredentials as boolean

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns true if the name and password currently set for this DMMemberAccount object match the .Mac credentials stored on the system.

removeGroupNamed(name as string) as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes the DMGroup with the given name from .Mac.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success.

removeSecondaryUserNamed(name as string) as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Removes the secondary user with the given name from .Mac.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success.

resetPassword(password as string, SecondaryUserNamed as string) as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Resets the password of the secondary user with the given name.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success.

secondaryUserNames as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Lists all secondary users owned by this .Mac member.

Notes: Returns a DMTransaction object whose isSuccessful method can be used to test for success and whose result method returns an Array of Strings on success.

servicesAvailableForAccount as DMTransactionMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The returned DMTransaction objects result method returns an array of string entries corresponding to available services for the .Mac account represented by this DMMemberAccount instance.

Notes:

If a given .Mac service is enabled for this account, then the array will contain a string equal to one of these String constants:

Service Constant	Meaning
kDMiDiskService	The account has iDisk storage associated with it.
kDMEmailService	The account has an email address along with the associated email storage.
16kDMWebHostingService	The account has web hosting capabilities through its iDisks Sites folder.
kDMiSyncService	The account has access to .Macs iSync- related functionality.

[Note: If the account credentials do not exist or some other error occurs, the returned DMTransactions `errorType` method can be used to identify the error.]

signUpNewMember

shared method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will launch the users default web browser and open the .Mac new member sign-up page, which is localized based on system preferences.

Notes: This method can be used when the user of the given application is not yet a .Mac member and cannot fully enjoy the applications features without a .Mac account.

signUpNewMemberWithApplicationID(appID as string)

shared method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will launch the users default web browser and open the .Mac new member sign-up page, which is localized based on system preferences.

Notes:

This method performs the same function as the `signUpNewMember` method, and additionally ensures that the owner of the provided application ID (if a member of the .Mac Affiliate Program) earns a commission whenever a user of their application becomes a paying .Mac member. For more information on the .Mac Affiliate Program, please visit

<http://www.mac.com/1/affiliates/faq.html>.

signUpURL as string

shared method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method provides access to the same localized URL that the `signUpNewMember` method loads in the default browser.

Notes: [Note: The URL returned by this method should not be hard-coded within an application, as it may change in the future.]

signUpURLWithApplicationID(appID as string) as string

shared method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Returns the URL for the .Mac sign-up page, with commission tracking enabled if the owner of the provided application ID is a member of the .Mac Affiliate Program.

Notes:

For more information on the .Mac Affiliate Program, please visit this website:
<http://www.mac.com/1/affiliates/faq.html>

[Note: The URL returned by this method should not be hard-coded within an application, as it may change in the future.]

transactionDelegate as DMTransactionDelegateMBS

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: The transaction delegate in use for all the transactions made by this object.

Notes:

This method is used to set the delegate object which will receive status messages from asynchronous transactions generated by the object that conforms to this protocol. The object passed in this method's delegate parameter must conform to the informal DMTransactionDelegate protocol. Transaction delegates receive their messages on the run loop originally used to create the given DMTransaction. It is safe to call this method to change the delegate as needed—since an in-flight DMTransaction object uses the settings that were in place at the time it was created, calling this method will not affect any transaction already in progress. A transaction delegate object does not receive callbacks for transactions executed synchronously. (Read and Write computed property)

upgradeAccount

method from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: This method will launch the users default web browser and open the appropriate .Mac member-

ship upgrade page, which is localized based on system preferences.

validateCredentials as integer

method from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: Use this method to check that the given account contains valid .Mac credentials.

Notes: The returned integer will correspond to one of the Status Constants defined in the Constants section of this document.

2.12.2 Constants

kDMBackupService = "Backup"

const from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of constants returned in the `DMMemberAccountMBS.servicesAvailableForAccount` method.

kDMEmailService = "Email"

const from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of constants returned in the `DMMemberAccountMBS.servicesAvailableForAccount` method.

Notes: The account has an email address along with the associated email storage.

kDMiDiskService = "iDisk"

const from class `DMMemberAccountMBS`, `DotMacSDK`, `MBS REALbasic DotMacKit Plugin (DotMacKit)`, Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of constants returned in the `DMMemberAccountMBS.servicesAvailableForAccount` method.

Notes: The account has iDisk storage associated with it.

kDMInsufficientStorage=102

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac account does not have sufficient disk space to accommodate the given operation.

kDMInvalidCredentials=101

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The .Mac credentials set for this object do not have access to a .Mac account.

kDMInvalidParameter=107

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: A user-provided parameter was invalid.

kDMiSyncService = "iSync"

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of constants returned in the DMMemberAccountMBS.servicesAvailableForAccount method.

Notes: The account has access to .Macs iSync- related functionality.

kDMNetworkError=103

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Unable to interact with .Mac because of a networking error or lack of network availability.

kDMResourceExists=105

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Indicates an error due to the pre-existence of a given resource.

kDMResourceNotFound=104

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: A required resource was not found.

kDMServiceBusy=106

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The given .Mac service was too busy to perform the requested operation and the operation should be retried later.

kDMSuccess=1

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: The operation was successful.

kDMUndefined=-1

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Used by individual methods as noted in this documents method descriptions.

kDMUnknownError=100

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of the DotMacKit status constants.

Notes: Unable to complete operation because of an unknown error.

kDMWebHostingService = "WebHosting"

const from class DMMemberAccountMBS, DotMacSDK, MBS REALbasic DotMacKit Plugin (DotMacKit), Plugin version: 9.7, not console safe, Mac OS X: Works, Windows: Does nothing, Linux x86: Does nothing.

Function: One of constants returned in the DMMemberAccountMBS.servicesAvailableForAccount method.

Notes: The account has web hosting capabilities through its iDisks Sites folder.

Chapter 3

List of all classes

• DMAccountMBS	72
• DMGroupMBS	44
• DMiDiskSessionMBS	47
• DMMemberAccountMBS	81
• DMMessageMBS	74
• DMMessagePublisherMBS	20
• DMMessageSubscriberMBS	11
• DMSecondaryUserMBS	16
• DMTopicMBS	36
• DMTransactionDelegateMBS	42
• DMTransactionMBS	28

Chapter 4

List of all global methods

- 2.5 LoadDotMacKitFrameworkMBS(path as folderitem) as boolean

36